



KYOTO IZUMI

~Hanging Instruction~

Thank you very much for purchasing KYOTO IZUMI WALLCOVERING products.
This product is delicate due to a natural textile wallpaper, so please note the following instruction for installing.

Always use putty of the same color as the substrate to ensure a smooth finish on the installation surface.

After installation, the color of the substrate may show through.

If necessary, use a color sealer to unify the color of the substrate.

Due to substrates such as veneer, discoloration or staining may occur over time.

Use a sealer that is suitable for the substrate, not just veneer. (Sealer treatment is recommended for all substrates).

The substrate must dry thoroughly before installing. This may cause peeling, discoloration or mould if you skip this process.

Follow the dilution rate specified by the glue manufacturer. Or we recommend to use of undiluted glue is recommended.

Try to avoid leaving the glue on for too long at least 5-10 minutes.

After gluing, be sure to fold the wallpaper and do not stack it on top of the wallpaper, as this may cause folding wrinkles.

Note not to get glue on the surface of the wallpaper.

Some materials may not release the glue or may lose their surface color if rubbed hard.

After installation, avoid sudden changes in room temperature due to peeling wallpaper.

e.g., from outside temperature or air conditioning.

This product is recommended to be about by sticking.

Please check the finish when the wallpaper has been installed.

Colors, patterns and textures may differ slightly between the actual product and the sample depending on the production lot.

Please consider this as part of the design from natural material and not a defect of the product.

Please contact us if you have any other inquiries.

info@kyoto-izumi.com